


**PLSD** プロタイプロングドリル ブラックタイプ (OX)  
Pro Type Straight Long Drills



**HSS OX 118° HH X シンニング h8**

*PLSD*

包装数量 1  
pcs

直径	溝長	全長
Dc	l	L
1.0	30	75
1.0	40	100
1.1	30	75
1.1	40	100
1.2	30	75
1.2	40	100
1.3	30	75
1.3	40	100
1.4	30	75
1.4	40	100
1.5	35	75
1.5	40	100
1.6	35	75
1.6	50	100
1.7	50	100
1.8	50	100
1.9	50	100
2.0	50	100
2.0	65	125
2.0	75	150
2.1	50	100
2.1	65	125
2.1	75	150
2.2	50	100
2.2	65	125
2.2	75	150
2.3	50	100
2.3	65	125
2.3	75	150
2.4	50	100
2.4	65	125
2.4	75	150

直径	溝長	全長
Dc	l	L
2.5	50	100
2.5	65	125
2.5	75	150
2.6	50	100
2.6	65	125
2.6	75	150
2.7	50	100
2.7	65	125
2.7	75	150
2.8	50	100
2.8	65	125
2.8	75	150
2.9	50	100
2.9	65	125
2.9	75	150
3.0	50	100
3.0	65	125
3.0	75	150
3.0	100	200
3.1	65	125
3.1	75	150
3.1	100	200
3.2	65	125
3.2	75	150
3.2	100	200
3.3	65	125
3.3	75	150
3.3	100	200
3.4	65	125
3.4	75	150
3.4	100	200
3.5	65	125

直径	溝長	全長
Dc	l	L
3.5	75	150
3.5	100	200
3.6	70	125
3.6	75	150
3.6	100	200
3.7	70	125
3.7	75	150
3.7	100	200
3.8	70	125
3.8	75	150
3.8	100	200
3.9	70	125
3.9	75	150
3.9	100	200
4.0	70	125
4.0	75	150
4.0	100	200
4.0	125	250
4.1	75	150
4.1	100	200
4.2	75	150
4.2	100	200
4.3	75	150
4.3	100	200
4.4	75	150
4.4	100	200
4.5	75	150
4.5	100	200
4.5	125	250
4.6	90	150
4.6	100	200
4.7	90	150

直径	溝長	全長
Dc	l	L
4.7	100	200
4.8	90	150
4.8	100	200
4.9	90	150
4.9	100	200
5.0	90	150
5.0	100	200
5.0	125	250
5.1	90	150
5.1	100	200
5.2	90	150
5.2	100	200
5.3	90	150
5.3	100	200
5.4	90	150
5.4	100	200
5.5	90	150
5.5	100	200
5.5	125	250
5.6	90	150
5.6	100	200
5.7	90	150
5.7	100	200
5.8	90	150
5.8	100	200
5.9	90	150
5.9	100	200
6.0	90	150
6.0	100	200
6.0	125	250
6.0	200	300