

SDL 左振れストレートドリル

型番	鋼 P	ステンレス鋼 M	鋳鉄 K	非鉄金属 N	耐熱合金 S	高硬度鋼 H
SDL	○	△	○	○		

○=最適 ○=適 △=可

- 左ねじれドリル
- 自動盤、スピンドルが左回転のものに使用いたします。



平面研削 D<2.45
円錐研削 D≥2.45



直径許容差
(0.1とび)
h8 公差

(0.05とび)
D<2 0~0.008
2≤D<5 0~0.01
5≤D<13 h8 公差

単位: mm

包装単位	最小包装単位
0.2~7.9	10本入り
8.0~13.0	5本入り



単位: mm				単位: mm				単位: mm			
在庫	直径 (φD)	溝長 (ℓ)	全長 (L)	在庫	直径 (φD)	溝長 (ℓ)	全長 (L)	在庫	直径 (φD)	溝長 (ℓ)	全長 (L)
○	0.3	3.5	20	○	2.2	33	58	○	4.1	54	83
○	0.35	5.5	24	○	2.25	33	58	○	4.15	54	83
○	0.4	5.5	24	○	2.3	33	58	○	4.2	54	83
○	0.45	7.5	27	○	2.35	35	61	○	4.25	54	83
○	0.5	7.5	27	○	2.4	35	61	○	4.3	54	83
○	0.55	8.5	30	○	2.45	35	61	○	4.35	56	86
○	0.6	8.5	30	○	2.5	35	61	○	4.4	56	86
○	0.65	10	32	○	2.55	37	64	○	4.45	56	86
○	0.7	10	32	○	2.6	37	64	○	4.5	56	86
○	0.75	11	34	○	2.65	37	64	○	4.55	56	86
○	0.8	11	34	○	2.7	37	64	○	4.6	56	86
○	0.85	13	36	○	2.75	39	67	○	4.65	59	89
○	0.9	13	36	○	2.8	39	67	○	4.7	59	89
○	0.95	18	40	○	2.85	42	71	○	4.75	59	89
○	1	18	40	○	2.9	42	71	○	4.8	59	89
○	1.05	20	42	○	2.95	42	71	○	4.85	62	92
○	1.1	20	42	○	3	42	71	○	4.9	62	92
○	1.15	20	42	○	3.05	42	71	○	4.95	62	92
○	1.2	20	42	○	3.1	42	71	○	5	62	92
○	1.25	22	45	○	3.15	42	71	△	5.05	62	92
○	1.3	22	45	○	3.2	42	71	○	5.1	62	92
○	1.35	23	48	○	3.25	45	73	△	5.15	64	95
○	1.4	23	48	○	3.3	45	73	○	5.2	64	95
○	1.45	23	48	○	3.35	45	73	△	5.25	64	95
○	1.5	23	48	○	3.4	45	73	○	5.3	64	95
○	1.55	25	50	○	3.45	45	73	△	5.35	64	95
○	1.6	25	50	○	3.5	45	73	○	5.4	64	95
○	1.65	25	50	○	3.55	48	76	△	5.45	64	95
○	1.7	25	50	○	3.6	48	76	○	5.5	64	95
○	1.75	28	52	○	3.65	48	76	△	5.55	67	98
○	1.8	28	52	○	3.7	48	76	○	5.6	67	98
○	1.85	28	52	○	3.75	48	76	△	5.65	67	98
○	1.9	28	52	○	3.8	48	76	○	5.7	67	98
○	1.95	29	55	○	3.85	51	79	△	5.75	67	98
○	2	29	55	○	3.9	51	79	○	5.8	67	98
○	2.05	29	55	○	3.95	54	83	△	5.85	67	98
○	2.1	29	55	○	4	54	83	○	5.9	67	98
○	2.15	33	58	○	4.05	54	83	△	5.95	70	102

○: 標準在庫 * : 特定代理店在庫 △: 在庫限り

単位：mm

単位：mm

在庫	直径 (φD)	溝長 (ℓ)	全長 (L)
◎	6	70	102
△	6.05	70	102
◎	6.1	70	102
△	6.15	70	102
◎	6.2	70	102
△	6.25	70	102
◎	6.3	70	102
△	6.35	73	105
◎	6.4	73	105
△	6.45	73	105
◎	6.5	73	105
△	6.55	73	105
◎	6.6	73	105
◎	6.7	73	105
◎	6.8	73	105
◎	6.9	73	105
◎	7	73	105
◎	7.1	75	108
◎	7.2	75	108
◎	7.3	75	108
◎	7.4	78	111
◎	7.5	78	111
◎	7.6	78	111
◎	7.7	81	114
◎	7.8	81	114
◎	7.9	81	114
◎	8	81	114
◎	8.1	84	117
◎	8.2	84	117
◎	8.3	84	117
◎	8.4	87	121
◎	8.5	87	121
◎	8.6	87	121
◎	8.7	87	121
◎	8.8	89	124
◎	8.9	89	124
◎	9	89	124
◎	9.1	89	124
◎	9.2	92	127
◎	9.3	92	127
◎	9.4	92	127
◎	9.5	92	127
◎	9.6	95	130
◎	9.7	95	130
◎	9.8	95	130
◎	9.9	95	130
◎	10	95	130
◎	10.1	98	133
◎	10.2	98	133
◎	10.3	98	133
◎	10.4	98	133
◎	10.5	100	137
◎	10.6	100	137
◎	10.7	100	137
△	10.8	103	140
△	10.9	103	140
◎	11	103	140
△	11.1	103	140
△	11.2	106	143
△	11.3	106	143
△	11.4	106	143

在庫	直径 (φD)	溝長 (ℓ)	全長 (L)
◎	11.5	106	143
△	11.6	109	146
△	11.7	109	146
△	11.8	109	146
△	11.9	109	146
◎	12	111	149
△	12.1	111	149
△	12.2	111	149
△	12.3	111	149
△	12.4	114	152
◎	12.5	114	152
△	12.6	114	152
△	12.7	114	152
△	12.8	114	152
△	12.9	114	152
◎	13	114	152

◎○：標準在庫 *：特定代理店在庫 △：在庫限り